

# Memory Module Specifications

## KSM24RD4/32MAI

32GB 2Rx4 4G x 72-Bit PC4-2400

CL17 Registered w/Parity 288-Pin DIMM

### DESCRIPTION

Kingston's KSM24RD4/32MAI is a 4G x 72-bit (32GB) DDR4-2400 CL17 SDRAM (Synchronous DRAM) registered w/ parity, 2Rx4, ECC, memory module, based on thirty-six 2G x 4-bit FBGA components. The SPD is programmed to JEDEC standard latency DDR4-2400 timing of 17-17-17 at 1.2V. Each 288-pin DIMM uses gold contact fingers. The electrical and mechanical specifications are as follows:

### FEATURES

- Power Supply: VDD=1.2V
- VDDQ = 1.2V
- VPP - 2.5V
- VDDSPD=2.25V to 2.75V
- Functionality and operations comply with the DDR4 SDRAM datasheet
- 16 internal banks
- Bank Grouping is applied, and CAS to CAS latency (tCCD\_L, tCCD\_S) for the banks in the same or different bank group accesses are available
- Data transfer rates: PC4-2400, PC4-2133, PC4-1866, PC4-1600
- Bi-Directional Differential Data Strobe
- 8 bit pre-fetch
- Burst Length (BL) switch on-the-fly BL8 or BC4(Burst Chop)
- Supports ECC error correction and detection
- On-Die Termination (ODT)
- Temperature sensor with integrated SPD
- This product is in compliance with the RoHS directive.
- Per DRAM Addressability is supported
- Internal Vref DQ level generation is available
- Write CRC is supported at all speed grades
- CA parity (Command/Address Parity) mode is supported

### SPECIFICATIONS

CL(IDD)	17 cycles
Row Cycle Time (tRCmin)	46.16ns(min.)
Refresh to Active/Refresh Command Time (tRFCmin)	350ns(min.)
Row Active Time (tRASmin)	32ns(min.)
Maximum Operating Power	*
UL Rating	94 V - 0
Operating Temperature	0° C to +85° C
Storage Temperature	-55° C to +100° C

\* See IDD Table (page 2)

### Module Assembly

**DRAM:** MICRON (A-DIE)




**RCD:** IDT

Continued >>

## IDD Specifications

Symbol	2400	Units
I <sub>DD0</sub>	1620	mA
I <sub>PP0</sub>	108	mA
I <sub>DD1</sub>	1890	mA
I <sub>DD2N</sub>	1800	mA
I <sub>DD2NT</sub>	1620	mA
I <sub>DD2P</sub>	1080	mA
I <sub>DD2Q</sub>	1620	mA
I <sub>DD3N</sub>	1980	mA
I <sub>PP3N</sub>	108	mA
I <sub>DD3P</sub>	1440	mA
I <sub>DD4R</sub>	3150	mA
I <sub>DD4W</sub>	3150	mA
I <sub>DD5R</sub>	1692	mA
I <sub>PP5R</sub>	144	mA
I <sub>DD6N</sub>	1080	mA
I <sub>DD6E</sub>	1260	mA
I <sub>DD6R</sub>	900	mA
I <sub>DD6A</sub>	720	mA
I <sub>DD6A</sub>	900	mA
I <sub>DD6A</sub>	1260	mA
I <sub>PP6X</sub>	180	mA
I <sub>DD7</sub>	3960	mA
I <sub>PP7</sub>	324	mA
I <sub>DD8</sub>	720	mA

## MODULE DIMENSIONS



The product images shown are for illustration purposes only and may not be an exact representation of the product.  
Kingston reserves the right to change any information at anytime without notice.