# Memory Module Specifications



## KF436C17BB2A/8

8GB 1G x 64-Bit DDR4-3600 CL17 288-Pin DIMM



### **SPECIFICATIONS**

CL(IDD)	17 cycles
Row Cycle Time (tRCmin)	45.75ns(min.)
Refresh to Active/Refresh Command Time (tRFCmin)	350ns(min.)
Row Active Time (tRASmin)	32ns(min.)
UL Rating	94 V - 0
Operating Temperature	0° C to +70° C
operating remperature	

## DESCRIPTION

Kingston FURY KF436C17BB2A/8 is a 1G x 64-bit (8GB) DDR4-3600 CL17 SDRAM (Synchronous DRAM) 1Rx8, memory module, based on eight 1G x 8-bit FBGA components per module. Each module kit supports Intel® Extreme Memory Profiles (Intel® XMP) 2.0. Each module has been tested to run at DDR4-3600 at a low latency timing of 17-21-21 at 1.35V. The SPDs are programmed to JEDEC standard latency DDR4-2400 timing of 17-17-17 at 1.2V. Each 288-pin DIMM uses gold contact fingers. The JEDEC standard electrical and mechanical specifications are as follows:

#### **FEATURES**

- Power Supply: VDD = 1.2V Typical
- VDDQ = 1.2V Typical
- VPP = 2.5V Typical
- VDDSPD = 2.2V to 3.6V
- On-Die termination (ODT)
- 16 internal banks; 4 groups of 4 banks each
- Bi-Directional Differential Data Strobe
- 8 bit pre-fetch
- Burst Length (BL) switch on-the-fly BL8 or BC4(Burst Chop)
- · Height 1.69" (43mm), w/heatsink


## **FACTORY TIMING PARAMETERS**

DDR4-2400 CL17-17-17 @1.2V • Default (JEDEC): • XMP Profile #1: DDR4-3600 CL17-21-21 @1.35V • XMP Profile #2: DDR4-3000 CL15-17-17 @1.35V


Continued >>




### **MODULE WITH HEAT SPREADER**



#### **MODULE DIMENSIONS**





# All measurements are in millimeters. (Tolerances on all dimensions are ±0.15 unless otherwise specified)

133.35
129.55

3.00

Ppn 1 Detail A Ppn 25 Ppn 47 Detail B Ppn 15 Ppn 17 Ppn 105 Ppn 105 Ppn 17 Ppn 105 Ppn 1

The product images shown are for illustration purposes only and may not be an exact representation of the product. Kingston reserves the right to change any information at anytime without notice.

### FOR MORE INFORMATION, GO TO KINGSTON.COM

All Kingston products are tested to meet our published specifications. Some motherboards or system configurations may not operate at the published Kingston FURY memory speeds and timing settings. Kingston does not recommend that any user attempt to run their computers faster than the published speed. Overclocking or modifying your system timing may result in damage to computer components.