

Memory Module Specifications

KSM24RD8/16MEI

16GB 2Rx8 2G x 72-Bit PC4-2400

CL17 Registered w/Parity 288-Pin DIMM

DESCRIPTION

Kingston's KSM24RD8/16MEI is a 2G x 72-bit (16GB) DDR4-2400 CL17 SDRAM (Synchronous DRAM) registered w/ parity, 2Rx8, ECC, memory module, based on eighteen 1G x 8-bit FBGA components. The SPD is programmed to JEDEC standard latency DDR4-2400 timing of 17-17-17 at 1.2V. Each 288-pin DIMM uses gold contact fingers. The electrical and mechanical specifications are as follows:

FEATURES

- Power Supply: VDD = 1.2V
- VDDQ = 1.2V
- VPP = 2.5V
- VDDSPD = 2.25V to 2.75V
- Functionality and operations comply with the DDR4 SDRAM datasheet
- 16 internal banks
- Bank Grouping is applied, and CAS to CAS latency (tCCD_L, tCCD_S) for the banks in the same or different bank group accesses are available
- Data transfer rates: PC4-2400, PC4-2133, PC4-1866, PC4-1600
- Bi-Directional Differential Data Strobe
- 8 bit pre-fetch
- Burst Length (BL) switch on-the-fly BL8 or BC4(Burst Chop)
- Supports ECC error correction and detection
- On-Die Termination (ODT)
- Temperature sensor with integrated SPD
- This product is in compliance with the RoHS directive.
- Per DRAM Addressability is supported
- Internal Vref DQ level generation is available
- Write CRC is supported at all speed grades
- CA parity (Command/Address Parity) mode is supported

SPECIFICATIONS

CL(IDD)	17 cycles
Row Cycle Time (tRCmin)	46.16ns(min.)
Refresh to Active/Refresh Command Time (tRFCmin)	350ns(min.)
Row Active Time (tRASmin)	32ns(min.)
Maximum Operating Power	*
UL Rating	94 V - 0
Operating Temperature	0° C to +85° C
Storage Temperature	-55° C to +100° C

*See IDD Specifications (page 2)

Module Assembly




DRAM: MICRON (E-DIE)
RCD: IDT

Continued >>

IDD Specifications

Symbol	2400	Units
I _{DD0}	657	mA
I _{PP0}	54	mA
I _{DD1}	765	mA
I _{DD2N}	612	mA
I _{DD2NT}	675	mA
I _{DD2P}	450	mA
I _{DD2Q}	540	mA
I _{DD3N}	864	mA
I _{PP3N}	54	mA
I _{DD3P}	666	mA
I _{DD4R}	1530	mA
I _{DD4W}	1377	mA
I _{DD5R}	747	mA
I _{PP5R}	72	mA
I _{DD6N}	612	mA
I _{DD6E}	828	mA
I _{DD6R}	378	mA
I _{DD6A}	154.8	mA
I _{DD6A}	378	mA
I _{DD6A}	558	mA
I _{PP6X}	90	mA
I _{DD7}	1836	mA
I _{PP7}	162	mA
I _{DD8}	450	mA

MODULE DIMENSIONS



The product images shown are for illustration purposes only and may not be an exact representation of the product.
Kingston reserves the right to change any information at anytime without notice.