

KVR1066D3D4R7SK3/24G

16GB (8GB 1024M x 72-Bit x 3 pcs.) PC3-8500

CL7 Registered w/Parity 240-Pin DIMM Kit

DESCRIPTION:

ValueRAM's KVR1066D3D4R7SK2/16G is a kit of three 1024M x 72-bit 8GB (8192MB) DDR3-1066MHz CL7 SDRAM (Synchronous DRAM) registered w/parity, dual-rank memory modules, based on thirty-six 512M x 4-bit DDR3-1066MHz FBGA components per module. Total kit capacity is 24GB. The SPDs are programmed to JEDEC standard latency 1066MHz timing of 7-7-7 at 1.5V. Each 240-pin DIMM uses gold contact fingers and requires +1.5V. The electrical and mechanical specifications are as follows:

FEATURES:

- JEDEC standard 1.5V \pm 0.075V Power Supply
- VDDQ = 1.5V \pm 0.075V
- 533MHz fCK for 1066Mb/sec/pin
- 8 independent internal bank
- Programmable CAS Latency: 6,7,8,9,10
- Programmable Additive Latency: 0, CL - 2, or CL - 1 clock
- Programmable CAS Write Latency(CWL) = 6(DDR3-1066)
- 8-bit pre-fetch
- Burst Length: 8 (Interleave without any limit, sequential with starting address "000" only), 4 with tCCD = 4 which does not allow seamless read or write [either on the fly using A12 or MRS]
- Bi-directional Differential Data Strobe
- Internal(self) calibration : Internal self calibration through ZQ pin (RZQ : 240 ohm \pm 1%)
- On Die Termination using ODT pin
- On-DIMM thermal sensor (Grade B)
- Average Refresh Period 7.8us at lower then TCASE 85°C, 3.9us at 85°C < TCASE . 95°C
- Asynchronous Reset
- PCB : Height 1.180" (30.00mm), double sided component

PERFORMANCE:

- | | |
|--|--------------------------------|
| <input checked="" type="checkbox"/> CL(IDD) | 7 cycles |
| <input checked="" type="checkbox"/> Row Cycle Time (tRCmin) | 50.625ns (min.) |
| <input checked="" type="checkbox"/> Refresh to Active/Refresh Command Time (tRFCmin) | 160ns (min.) |
| <input checked="" type="checkbox"/> Row Active Time (tRASmin) | 37.5ns (min.) |
| <input checked="" type="checkbox"/> Power | 4.110 W (operating per module) |
| <input checked="" type="checkbox"/> UL Rating | 94 V - 0 |
| <input checked="" type="checkbox"/> Operating Temperature | 0° C to 85° C |
| <input checked="" type="checkbox"/> Storage Temperature | -55° C to +100° C |

MODULE DIMENSIONS:

Units : Millimeters

