

KVR1333D3D4R9SL/8G

8GB 2Rx4 1G x 72-Bit PC3-10600

CL9 Registered w/Parity VLP 240-Pin DIMM

DESCRIPTION

This document describes ValueRAM's 1G x 72-bit (8GB) DDR3-1333 CL9 SDRAM (Synchronous DRAM), registered w/ parity, 2Rx4 ECC VLP (Very Low Profile) memory module, based on eighteen 1G x 4-bit FBGA components in (stacked) DDP packages (thirty-six 512M x 4 bit devices). The SPD is programmed to JEDEC standard latency DDR3-1333 timing of 9-9-9. This 240-pin DIMM uses gold contact fingers. The electrical and mechanical specifications are as follows:

FEATURES

- JEDEC standard 1.5V (1.425V ~1.575V) Power Supply
- VDDQ = 1.5V (1.425V ~ 1.575V)
- 667MHz fCK for 1333Mb/sec/pin
- 8 independent internal bank
- Programmable CAS Latency: 9, 8, 7, 6
- Programmable Additive Latency: 0, CL - 2, or CL - 1 clock
- Programmable CAS Write Latency(CWL) = 7 (DDR3-1333)
- 8-bit pre-fetch
- Burst Length: 8 (Interleave without any limit, sequential with starting address "000" only), 4 with tCCD = 4 which does not allow seamless read or write [either on the fly using A12 or MRS]
- Bi-directional Differential Data Strobe
- Internal(self) calibration : Internal self calibration through ZQ pin (RZQ : 240 ohm ± 1%)
- On Die Termination using ODT pin
- On-DIMM thermal sensor (Grade B)
- Average Refresh Period 7.8us at lower than TCASE 85°C, 3.9us at 85°C < TCASE ≤ 95°C
- Asynchronous Reset
- Includes Full-DIMM Heat Spreader
- PCB : Height 0.740" (18.75mm), double sided component

SPECIFICATIONS


CL(IDD)	9 cycles
Row Cycle Time (tRCmin)	49.5ns (min.)
Refresh to Active/Refresh Command Time (tRFCmin)	160ns (min.)
Row Active Time (tRASmin)	36ns (min.)
Power (Operating)	3.306 W*
UL Rating	94 V - 0
Operating Temperature	0° C to 85° C
Storage Temperature	-55° C to +100° C

*Power will vary depending on the SDRAM and Register/PLL used.


Continued >>

MODULE DIMENSIONS:


Front




Back




Detail of Contacts A




Detail of Contacts B



Detail of Contacts C



Side



Side

