

KVR13LR9S4K4/16

16GB (4GB 512M x 72-Bit x 4 pcs.) PC3L-10600
CL9 Registered w/Parity 240-Pin DIMM Kit

DESCRIPTION

ValueRAM's KVR13LR9S4K4/16 is a kit of four 512M x 72-bit (4GB) DDR3L-1333 CL9 SDRAM (Synchronous DRAM), low voltage, registered w/parity, 1Rx4 ECC memory modules, based on eighteen 512M x 4-bit FBGA components. Total kit capacity is 16GB. The SPDs are programmed to JEDEC standard latency DDR3-1333 timing of 9-9-9 at 1.35V and 1.5V. Each 240-pin DIMM uses gold contact fingers. The electrical and mechanical specifications are as follows:

FEATURES

- JEDEC standard 1.35V (1.28V ~ 1.45V) and 1.5V (1.425V ~ 1.575V) Power Supply
- VDDQ = 1.35V (1.28V ~ 1.45V) and 1.5V (1.425V ~ 1.575V)
- 667MHz fCK for 1333Mb/sec/pin
- 8 independent internal bank
- Programmable CAS Latency: 9, 8, 7, 6
- Programmable Additive Latency: 0, CL - 2, or CL - 1 clock
- Programmable CAS Write Latency(CWL) = 7 (DDR3-1333)
- 8-bit pre-fetch
- Burst Length: 8 (Interleave without any limit, sequential with starting address "000" only), 4 with tCCD = 4 which does not allow seamless read or write [either on the fly using A12 or MRS]
- Bi-directional Differential Data Strobe
- Internal(self) calibration : Internal self calibration through ZQ pin (RZQ : 240 ohm ± 1%)
- On Die Termination using ODT pin
- On-DIMM thermal sensor (Grade B)
- Average Refresh Period 7.8us at lower than TCASE 85°C, 3.9us at 85°C < TCASE ≤ 95°C
- Asynchronous Reset
- PCB : Height 1.180" (30.00mm), double sided component


SPECIFICATIONS

CL(IDD)	9 cycles
Row Cycle Time (tRCmin)	49.5ns (min.)
Refresh to Active/Refresh Command Time (tRFCmin)	160ns (min.)
Row Active Time (tRASmin)	36ns (min.)
Maximum Operating Power	(1.35V) = 5.040 W* (1.50V) = 6.006 W*
UL Rating	94 V - 0
Operating Temperature	0° C to 85° C
Storage Temperature	-55° C to +100° C

*Power will vary depending on the SDRAM and Register/PLL used.

Continued >>

MODULE DIMENSIONS:



(units = millimeters)

