

Memory Module Specifications

KVR800D2S6K2/2G

2GB (1GB 1Rx8 128M x 64-Bit x 2 pcs.)
DDR2-800 CL6 200-Pin SODIMM Kit

DESCRIPTION

ValueRAM's KVR800D2S6K2/2G is a kit of two 128M x 64-bit (1GB) DDR2-800 CL6 SDRAM (Synchronous DRAM) 1Rx8 memory modules, based on eight 128M x 8-bit FBGA components per module. Total kit capacity is 2GB. Each 200-pin SODIMM uses gold contact fingers and requires +1.8V. The electrical and mechanical specifications are as follows:

SPECIFICATIONS

Clock Cycle Time (tCK)	2.5ns (min.) / 8ns (max.)
Row Cycle Time (tRCmin)	60ns (min.)
Refresh to Active/Refresh Command Time (tRFCmin)	127.5ns (min.)
Row Active Time (tRASmin)	45ns (min.) / 70,000 (max.)
Single Power Supply of	+1.8V (+/- .1V)
Power Operating (per module)	1.224 W (Approx.*)
UL Rating	94 V - 0

Note: The module described in this data sheet is one of several configurations available under this part number. While all configurations are compatible, the DRAM combination and/or the module height may vary from what is described here.

Figure 1: KVR800D2S6K2/2G 200-Pin SODIMM

