



SOLID STATE DRIVE  
 FLASH STORE  
 DURABLE  
 PC MEMORY  
 FLASH STORE  
 SUPGRADE KIT  
 FLASH STORE  
 SOLID STATE DRIVE

## SSDNow E100

### FEATURES/BENEFITS

- > **Performance** — higher IOPS for multi-user environments
- > **Endurance** — Data Integrity Protection featuring DuraClass™ Technology
- > **Dependable** — RAISE™ for advanced data reliability
- > **Durable** — DuraWrite optimizes writes to extend endurance
- > **Warranty/support** — three-year warranty with free technical support

### SPECIFICATIONS

- > **Form factor** 2.5"
- > **Interface** SATA Rev. 3.0 (6Gb/s) – with backwards compatibility to SATA Rev. 2.0 (3Gb/s)
- > **Capacities**<sup>1</sup> 100GB, 200GB, 400GB
- > **Controller** SandForce – SF2582
- > **Encryption** Automatic Encryption (AES 128bit)
- > **Sequential Read/Write**<sup>2</sup>
  - SATA Rev. 3.0 – 100GB – up to: 535/500MB/s
  - 200GB – up to: 535/500MB/s
  - 400GB – up to: 535/500MB/s
- > **Maximum 4k Read/Write**<sup>2</sup>
  - 100GB – up to 85,000/79,000 IOPS
  - 200GB – up to 85,000/76,000 IOPS
  - 400GB – up to 74,000/37,000 IOPS
- > **Random 4k Read/Write**<sup>2</sup>
  - 100GB – up to: 42,000/78,000 IOPS
  - 200GB – up to: 59,000/76,000 IOPS
  - 400GB – up to: 52,000/31,000 IOPS
- > **Enterprise SMART Tools** reliability tracking, usage statistics, life remaining, wear leveling, temperature
- > **Total Bytes Written (TBW)**<sup>3</sup>
  - 100GB – 1241TB11 DWPD<sup>4</sup>
  - 200GB – 2483TB11 DWPD<sup>4</sup>
  - 400GB – 3906TB 9 DWPD<sup>4</sup>
- > **Power Failure Support** Tantalum capacitors
- > **Power Consumption**
  - 1.18 W Idle / 1.18 W Avg / 1.22 W (MAX) Read / 3.23 W (MAX) Write
- > **Storage temperature** -40 ~ 85°C
- > **Operating temperature** 0 ~ 70°C
- > **Dimensions** 69.9mm x 100mm x 7mm
- > **Weight** 96.6 grams
- > **Vibration operating** 2.17G Peak (7–800Hz)
- > **Vibration non-operating** 20G Peak (10–2000Hz)
- > **MTBF** 1 million hours
- > **Guaranteed** three-year warranty with free technical support



### KINGSTON PART NUMBERS

SE100S37/100G  
 SE100S37/200G  
 SE100S37/400G

<sup>1</sup> Some of the listed capacity on a Flash storage device is used for formatting and other functions and thus is not available for data storage. As such, the actual available capacity for data storage is less than what is listed on the products. For more information, go to Kingston's Flash Memory Guide at [kingston.com/flashguide](http://kingston.com/flashguide)

<sup>2</sup> Based on "out-of-box performance." Speed may vary due to host hardware, software and usage.

<sup>3</sup> Total Bytes Written (TBW) is derived from the JEDEC Workload (JESD219A).

<sup>4</sup> Drive Writes Per Day (DWPD)

THIS DOCUMENT SUBJECT TO CHANGE WITHOUT NOTICE

©2013 Kingston Technology Corporation, 17600 Newhope Street, Fountain Valley, CA 92708 USA. All rights reserved. All trademarks and registered trademarks are the property of their respective owners. MKD-235.2US

