



DC600M 2.5" SATA Enterprise SSD

6Gbps SATA 3.0 storage for mixed-use workloads

Kingston's DC600M SSD is a fourth-generation data center SATA 3.0, 6Gbps SSD with 3D TLC NAND intended for "mixed use" workloads. The DC600M is suited for use in high-volume rack-mount servers and includes hardware-based on-board PLP. Via power loss capacitors, DC600M protects data against unexpected power failure to reduce the possibility of data loss and ensure that the drive will successfully re-initialise on the next power-up of the system. DC600M is designed to deliver latency and IOPS consistency for system integrators, hyperscale data centers and cloud service providers.

Capacities available from 480GB-7680GB¹ to meet your data storage requirements.

- Designed for data center environments
- Hardware-based power loss protection
- Latency and IOPS consistency
- Capacities up to 7680GB¹

Key Features

- Designed for data center environments
 Optimised to meet the high demands of server RAID applications with low latency and IO consistency as the key design criteria.
- Hardware-based PLP
 Power loss capacitors to protect user data against unexpected power loss and enhance performance.
- Delivers excellent quality of service (QoS)²
 Optimised performance predictability to meet service-level agreements (SLAs).
- Capacities up to 7680GB
 Upgrade and manage storage with capacities up to 7680GB.¹

Specifications

Form factor	2.5 inch
Interface	SATA Rev. 3.0 (6Gb/s) – with backwards compatibility to SATA Rev. 2.0 (3Gb/s)
Capacities ¹	480GB, 960GB, 1920GB, 3840GB, 7680GB
NAND	3D TLC
Sequential Read/Write	480GB – 560MBs/470MBs 960GB – 560MBs/530MBs 1,920GB – 560MBs/530MBs 3,840GB – 560MBs/530MBs 7680GB – 560MBs/530MBs
Steady-state 4k random read/write	480GB – 94,000/41,000 IOPS 960GB – 94,000/65,000 IOPS 1920GB – 94,000/78,000 IOPS 3840GB – 94,000/59,000 IOPS 7680GB – 94,000/34,000 IOPS

Quality of service (latency) ^{3, 4, 5} (99.999)	Read/Write 480GB – 180/110 uSec 960GB – 3840GB – 200/300 uSec 7680GB – 240/170 uSec
Typical latency - read/write	<200 μs / <30 us ^{3, 4, 5}
Hot-plug capable	Static and dynamic wear levelling
Enterprise SMART tools	Reliability tracking, usage statistics, life remaining, wear levelling, temperature
Hardware-based power loss protection Endurance ⁶	480GB – 876TBW, 1 DWPD (5 years), 1.66 DWPD (3 years) 960GB – 1752TBW, 1 DWPD (5 years), 1.66 DWPD (3 years) 1920GB – 3504TBW, 1 DWPD (5 years), 1.66 DWPD (3 years) 3840GB – 7008TBW, 1 DWPD (5 years), 1.66 DWPD (3 years) 7680GB – 14016TBW, 1 DWPD (5 years), 1.66 DWPD (3 years)
Power consumption	Idle: 1.30W Average: 1.45W Max read: 1.6W Max write: 3.6W
Storage temperature	-40°C ~ 85°C
Operating temperature	0°C ~ 70°C
Dimensions	69.9mm x 100mm x 7mm
Weight	92.34g
Vibration operating	2.17G Peak (7–800Hz)
Vibration non-operating	20G peak (10–2000Hz)

MTBF	2 million hours
UBER	$\leq 10^{-17}$
Warranty/support	Limited 5-year warranty with free technical support ⁷

Part Numbers

SEDC600M

SEDC600M/480G
SEDC600M/960G
SEDC600M/1920G
SEDC600M/3840G
SEDC600M/7680G

Product Image



1. Some of the listed capacity on a Flash storage device is used for formatting and other functions and thus is not available for data storage. As such, the actual available capacity for data storage is less than what is listed on the products. For more information, go to Kingston's [Flash Memory Guide](#).
2. Quality of service (QoS) of an SSD refers to the consistency and predictability of latency (response time) and IOPS (IOs per second) performance while servicing a read/write workload. QoS metrics demonstrate that, given a worst-case workload tested over a period of time, an SSD's latency and IOPS profiles stay within a specified range without having unexpected outliers that cause a sudden drop in application performance.
3. Measurement taken once the workload has reached steady state but including all background activities required for normal operation and data reliability.
4. Based on 1920GB capacity.
5. Workload based on FIO, random aligned 4KB QD=1 workload. Quality of service is measured as the time taken for 99.999 percentile of commands to finish the round trip from host to drive and to host. Typical latency is measured as the time taken for 99.9 percentile of commands to finish the round trip from host to drive and to host.
6. [Total Bytes Written](#) (TBW) and Drives Writes Per Day (DWPD) derived from the JEDEC Enterprise Workload (JESD219A).
7. Five-year conditional SSD warranty based on which of the following events occurs first: (i) five (5) years from the date of purchase by the original end user customer; (ii) when the usage of a SATA SSD as measured by Kingston's implementation of the SMART attribute 231, labelled as "SSD Wear Indicator", reaches a normalised value of one (1) as indicated by Kingston's SSD Manager ("KSM").



THIS DOCUMENT SUBJECT TO CHANGE WITHOUT NOTICE.

©2024 Kingston Technology Europe Co LLP and Kingston Digital Europe Co LLP, Kingston Court, Brooklands Close, Sunbury-on-Thames, Middlesex, TW16 7EP, England. Tel: +44 (0) 1932 738888 Fax: +44 (0) 1932 785469 All rights reserved. All trademarks and registered trademarks are the property of their respective owners. MKD-04032024